

KKT INDUSTRIAL GASKETS

DIMENSIONS FOR SPIRAL-WOUND GASKETS USED WITH PN DESIGNATED FLANGES BS EN 1514-2

FLANGES SIZE		D1	D2	D3		D4						
DN MM	NPS In.	PN 10 - PN 160	PN 10 - PN 160	PN 10 - PN 40	PN 63 - PN 160	PN 10	PN 16	PN 25	PN 40	PN 63	PN 100	PN 160
10	¼	18	24	35.5	35.5	46	46	46	46	56	56	56
15	½	23	29	40.5	40.5	51	51	51	51	61	61	61
20	¾	28	34	47.5	-	61	61	61	61	-	-	-
25	1	35	41	54.5	54.5	71	71	71	71	82	82	82
32	1 ¼	43	49	62.5	-	82	82	82	82	-	-	-
40	1 ½	50	56	69.5	69.5	92	92	92	92	103	103	103
50	2	61	70	87.5	87.5	107	107	107	107	113	119	119
65	2 ½	77	86	103.5	107.5	127	127	127	127	137	143	143
80	3	90	99	116.5	120.5	142	142	142	142	148	154	154
100	4	115	127	144.5	148.5	162	162	168	168	174	180	180
125	5	140	152	173.5	177.5	192	192	194	194	210	217	217
150	6	167	179	200.5	204.5	218	218	224	224	247	257	257
200	8	216	228	249.5	253.5	273	273	284	290	309	324	324
250	10	267	279	304.5	308.5	327	329	340	352	364	391	388
300	12	318	330	355.5	359.5	377	384	400	417	424	458	458
350	14	360	376	401.5	405.5	437	444	457	474	486	512	-
400	16	410	422	451.5	457.5	488	495	514	546	543	572	-
500	20	510	522	551.5	557.5	593	617	624	628	657	704	-
600	24	610	622	651.5	657.5	695	734	731	747	764	813	-
700	28	710	722	757.5	763.5	810	804	833	852	879	950	-
800	32	810	830	865.5	871.5	917	911	942	974	988	-	-
900	36	910	930	965.5	971.5	1017	1011	1042	1084	1108	-	-
1000	40	1010	1030	1075.5	1081.5	1124	1128	1154	1194	-	-	-

DIMENSION IN MILLIMETER