

KKT INDUSTRIAL GASKETS

Pressure nominal (PN) indicates the approximate pressure rating in bars.
The bar is the unit of pressure, and 1 bar is equal to 14.5 psi or 100 kilopascals (kPa)

PN6

N-Bore		Full Face (mm)					IBC (mm)	
in	mm	OD	ID	Holes	Dia.	P.C.D.	OD	ID
	10	75	18	4	11	50	39	18
0.5	15	80	22	4	11	55	44	22
0.8	20	90	28	4	11	65	54	28
1	25	100	35	4	11	75	64	35
1.3	32	120	43	4	14	90	76	43
1.5	40	130	49	4	14	100	86	49
2	50	140	61	4	14	110	96	61
2.5	65	160	77	4	14	130	116	77
3	80	190	90	4	18	150	132	90
4	100	210	115	4	18	170	152	115
5	125	240	141	8	18	200	182	141
6	150	265	169	8	18	225	207	169
8	200	320	220	8	18	280	226	220
10	250	375	274	12	18	335	317	274
12	300	440	325	12	22	395	373	325
14	350	490	368	12	22	445	423	368
16	400	540	420	16	22	495	473	420
18	450	595	470	16	22	550	528	470
20	500	645	520	20	22	600	578	520
24	600	755	620	20	26	705	679	620

The company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company

Mobile No:7010595641

E-mail Id:kktindustrialgaskets@gmail.com

PN10

N-Bore		Full Face (mm)					IBC (mm)	
in	mm	OD	ID	Holes	Dia.	P.C.D.	OD	ID
	10	90	18	4	14	60	45	18
0.5	15	95	22	4	14	65	50	22
0.8	20	105	28	4	14	75	60	28
1	25	115	35	4	14	85	70	35
1.3	32	140	43	4	18	100	82	43
1.5	40	150	49	4	18	110	92	49
2	50	165	61	4	18	125	107	61
2.5	65	185	77	8	18	145	127	77
3	80	200	90	8	18	160	142	90
4	100	220	115	8	18	180	162	115
5	125	250	141	8	18	210	192	141
6	150	285	169	8	22	240	218	169
8	200	340	220	8	22	295	273	220
10	250	395	274	12	22	350	328	274
12	300	445	325	12	22	400	378	325
14	350	505	356	16	22	460	438	356
16	400	565	407	16	26	515	489	407
18	450	615	458	20	26	565	539	458
20	500	670	508	20	26	620	594	508
24	600	780	610	20	30	725	695	610
28	700	895	712	24	30	840	810	712
32	800	1015	813	24	33	950	917	813
36	900	1115	915	28	33	1050	1017	915
40	1000	1230	1016	28	36	1160	1124	1016
	1100	1340	1120	32	39	1270	1231	1120
48	1200	1455	1220	32	39	1380	1341	1220
56	1400	1675	1420	36	42	1590	1548	1420
60	1500	1785	1520	36	42	1700	1658	1520
	1600	1915	1620	40	48	1820	1775	1620
	1800	2115	1820	44	48	2020	1972	1820
	2000	2325	2020	48	48	2230	2182	2020

PN16

N-Bore		Full Face (mm)					IBC (mm)	
in	mm	OD	ID	Holes	Dia.	P.C.D.	OD	ID
	10	90	18	4	14	60	45	18
0.5	15	95	22	4	14	65	50	22
0.8	20	105	28	4	14	75	60	28
1	25	115	35	4	14	85	70	35
1.3	32	140	43	4	18	100	82	43
1.5	40	150	49	4	18	110	92	49
2	50	165	61	4	18	125	107	61
2.5	65	185	77	8	18	145	127	77
3	80	200	90	8	18	160	142	90
4	100	220	115	8	18	180	162	115
5	125	250	141	8	18	210	192	141
6	150	285	169	8	22	240	218	169
8	200	340	220	12	22	295	273	220
10	250	405	274	12	26	355	329	274
12	300	460	325	12	26	410	384	325
14	350	520	356	16	26	470	444	356
16	400	580	407	16	30	525	492	407
18	450	640	458	20	30	585	555	458
20	500	715	508	20	33	650	617	508
24	600	840	610	20	36	770	734	610
28	700	910	712	24	36	840	804	712
32	800	1025	813	24	39	950	911	813
36	900	1125	915	28	39	1050	1011	915
40	1000	1255	1016	28	42	1170	1128	1016
	1100	1355	1120	32	42	1270	1228	1120
48	1200	1485	1220	32	48	1390	1342	1220
56	1400	1685	1420	36	48	1590	1542	1420
60	1500	1820	1520	36	56	1710	1654	1520
	1600	1930	1620	40	56	1820	1764	1620
	1800	2130	1820	44	56	2020	1964	1820
	2000	2345	2020	48	62	2230	2168	2020

PN25

N-Bore		Full Face (mm)					IBC (mm)	
	mm	OD	ID	Holes	Dia.	P.C.D.	OD	ID
	10	90	18	4	14	60	45	18
0.5	15	95	22	4	14	65	50	22
0.8	20	105	28	4	14	75	60	28
1	25	115	35	4	14	85	70	35
1.3	32	140	43	4	18	100	82	43
1.5	40	150	49	4	18	110	92	49
2	50	165	61	4	18	125	107	61
2.5	65	185	77	8	18	145	127	77
3	80	200	90	8	18	160	142	90
4	100	220	115	8	18	180	162	115
5	125	250	141	8	18	210	192	141
6	150	285	169	12	22	240	218	169
8	200	340	220	12	22	295	273	220
10	250	405	274	12	26	355	329	274
12	300	460	325	16	26	410	384	325
14	350	520	356	16	26	470	444	356
16	400	620	407	16	36	550	514	407
18	450	670	458	20	36	600	564	458
20	500	730	508	20	36	660	624	508
24	600	845	610	20	39	770	731	610
28	700	960	712	24	42	875	833	712
32	800	1085	813	24	48	990	942	813
36	900	1185	915	28	48	1090	1042	915
40	1000	1320	1016	28	56	1210	1154	1016
	1100	1420	1120	32	56	1310	1254	1120
48	1200	1530	1220	32	56	1420	1364	1220
56	1400	1755	1420	36	62	1640	1578	1420
60	1500	1865	1520	36	62	1750	1688	1520
	1600	1975	1620	40	62	1860	1798	1620
	1800	2195	1820	44	70	2070	2000	1820
	2000	2425	2020	48	70	2300	2230	2020

PN40

N-Bore		Full Face (mm)					IBC (mm)	
in	mm	OD	ID	Holes	Dia.	P.C.D.	OD	ID
	10	90	18	4	14	60	45	18
0.5	15	95	22	4	14	65	50	22
0.8	20	105	28	4	14	75	60	28
1	25	115	35	4	14	85	70	35
1.3	32	140	43	4	18	100	82	43
1.5	40	150	49	4	18	110	92	49
2	50	165	61	4	18	125	107	61
2.5	65	185	77	8	18	145	127	77
3	80	200	90	8	18	160	142	90
4	100	235	115	8	22	190	168	115
5	125	270	141	8	26	220	194	141
6	150	300	169	8	26	250	224	169
8	200	375	220	12	30	320	290	220
10	250	450	274	12	33	385	352	274
12	300	515	325	16	33	450	417	325
14	350	580	356	16	36	510	474	356
16	400	660	407	16	39	585	546	407
18	450	685	458	20	39	610	571	458
20	500	755	508	20	42	670	628	508
24	600	890	610	20	48	795	747	610
28	700	995	710	24	48	900	852	710
32	800	1140	820	24	56	1030	974	820
36	900	1250	910	28	56	1140	1084	910
40	1000	1360	1010	28	56	1250	1194	1010

PN63

N-Bore		Full Face (mm)					IBC (mm)	
in	mm	OD	ID	Holes	Dia.	P.C.D.	OD	ID
	10	N/A	N/A	N/A	N/A	N/A	56	18
0.5	15	N/A	N/A	N/A	N/A	N/A	61	21
0.8	20	N/A	N/A	N/A	N/A	N/A	72	25
1	25	N/A	N/A	N/A	N/A	N/A	82	30
1.3	32	N/A	N/A	N/A	N/A	N/A	88	41
1.5	40	N/A	N/A	N/A	N/A	N/A	103	47
2	50	N/A	N/A	N/A	N/A	N/A	113	59
2.5	65	N/A	N/A	N/A	N/A	N/A	138	73
3	80	N/A	N/A	N/A	N/A	N/A	148	86
4	100	N/A	N/A	N/A	N/A	N/A	174	110
5	125	N/A	N/A	N/A	N/A	N/A	210	135
6	150	N/A	N/A	N/A	N/A	N/A	247	163
8	200	N/A	N/A	N/A	N/A	N/A	309	210
10	250	N/A	N/A	N/A	N/A	N/A	364	264
12	300	N/A	N/A	N/A	N/A	N/A	424	314
14	350	N/A	N/A	N/A	N/A	N/A	486	360
16	400	N/A	N/A	N/A	N/A	N/A	543	415

PN100

N-Bore		Full Face (mm)					IBC (mm)	
in	mm	OD	ID	Holes	Dia.	P.C.D.	OD	ID
	10	N/A	N/A	N/A	N/A	N/A	56	18
0.5	15	N/A	N/A	N/A	N/A	N/A	61	22
0.8	20	N/A	N/A	N/A	N/A	N/A	72	28
1	25	N/A	N/A	N/A	N/A	N/A	82	35
1.3	32	N/A	N/A	N/A	N/A	N/A	88	43
1.5	40	N/A	N/A	N/A	N/A	N/A	103	49
2	50	N/A	N/A	N/A	N/A	N/A	120	61
2.5	65	N/A	N/A	N/A	N/A	N/A	145	77
3	80	N/A	N/A	N/A	N/A	N/A	155	90
4	100	N/A	N/A	N/A	N/A	N/A	180	115
5	125	N/A	N/A	N/A	N/A	N/A	217	141
6	150	N/A	N/A	N/A	N/A	N/A	257	169
8	200	N/A	N/A	N/A	N/A	N/A	324	220
10	250	N/A	N/A	N/A	N/A	N/A	391	274
12	300	N/A	N/A	N/A	N/A	N/A	458	325
14	350	N/A	N/A	N/A	N/A	N/A	512	368
16	400	N/A	N/A	N/A	N/A	N/A	627	420
18	450	N/A	N/A	N/A	N/A	N/A	704	470
20	500	N/A	N/A	N/A	N/A	N/A	813	520
24	600	N/A	N/A	N/A	N/A	N/A	950	620